

# SP PRO to SP LINK wireless link Quick start



**PLEASE NOTE:** Full installation instructions can be found on the USB stick provided in the "Application Notes" directory.

## Quick Start for fitting wireless link to SP PRO Series II only.

If you are using a series I inverter refer to full installation instructions on the USB stick.

1. Remove the stub antennas from the end of the ProBee-ZS10 adaptor and the ProBee-ZU10 adaptor (if fitted) and replace them with the di-pole antennas provided.
2. Using SP LINK check that the Communication Port 1 Baud rate is 57600. This is the default setting and should be correct if not changed during installation of the SP PRO.
3. Plug the ProBee-ZS10 adaptor into the DB9 connector at the base of the SP PRO inverter. Lightly tighten the retaining screws on the ZS10.
4. Turn ON the ON/OFF switch on the side of the ProBee-ZS10. The green "Power" LED will illuminate on the front panel of the ProBee-ZS10.
5. Install SP LINK software found on the USB stick provided. (If not already installed). SP LINK must be version 6.2 or greater.
6. Run SP LINK and create a site file following the instructions in the SP LINK manual (found in the "help" menu of SP LINK).
7. Plug the ProBee ZU10 into the USB port on the computer. The blue LED will light up on the ProBee ZU10.
8. The device will appear as "Zigbee wireless connection" in the list of available COM ports in SP LINK under "connection settings" in the "site information" tab.
9. Select "Connect" in the "Connection" menu and connect to the SP PRO inverter.



Device plugged into  
SP PRO

Device plugged  
into USB on  
Computer



## Additional Information

Selectronic web site – <http://www.selectronic.com.au> or contact the Selectronic Sales Team.